



99



00



10



40



35



30



01



24



25



LUCY

Apparecchio a soffitto in tre varianti: Acciaio, Alluminio e Nylon
Ceiling luminaire in three variants: Steel, Aluminum and Nylon

DESCRIZIONE DESCRIZIONE

Grazie alla cura nella selezione dei materiali e all'elevata protezione dalla corrosione, Lucy è la scelta ideale per installazioni in zone costiere o marine. L'appliche del modello Lucy è disponibile in nylon, alluminio verniciato o acciaio inox AISI316L. Disponibile nelle versioni incasso a muro, incasso a pavimento ed applique sia a muro che a soffitto, Lucy unisce versatilità e resistenza per un'illuminazione durevole e affidabile.

Due to the careful selection of materials and high corrosion protection, Lucy is the ideal choice for installations in coastal or marine areas. The wall lamp of model Lucy is available in nylon, painted aluminum or stainless steel AISI316L. Available in recessed wall, floor and ceiling versions, Lucy combines versatility and resistance for durable and reliable lighting.

INSTALLAZIONE INSTALLATION

Installazione a soffitto

Ceiling installation

SCHERMO SCREEN

Vetro extrachiario temprato

Extra clear tempered glass

GUARNIZIONI SEALS

EPDM

EPDM

VITERIA SCREWS

Acciaio inox A2

Stainless steel A2

VERNICIATURA FINISHING

Polvere poliestere stabilizzata ai raggi UV con trattamento anticorrosione

Anti-corrosive UV stabilized polyester powder







**CONFIG.
CODICE**
CODE
CONFIG.

▲ → **H=2700K**
W=3000K
N=4000K

**VERSIONE IN
TENSIONE**
CONSTANT
VOLTAGE



3,5W CON DRIVER REMOTO 24Vdc
3,5W REMOTE DRIVER 24Vdc

**VERSIONE
220-240V**
220-240V
VERSION

**DRIVER INCORPORATO/
ALIMENTAZIONE DIRETTA**
BUILT-IN DRIVER/DIRECT AC

Ø160

60



IP 66

IK 07



APPARECCHIO CON COPERTURA IN ACCIAIO
24VDC
LUMINAIRE WITH STEEL COVER
24VDC



CODICE CODE	FASCIO BEAM	WATT	SORGENTE SOURCE	APPARECCHIO FIXTURE	ALIMENTAZIONE POWER SUPPLY	CL	IP	IK	CRI
1050W/▲RRCVO	 DIFFUSO/110° DIFFUSED/110°	3,5W	500 lm	180 lm	24Vdc	III	66	07	>80

VO = VETRO EXTRACHIARO OPALE TEMPRATO - VO = EXTRA CLEAR OPAL TEMPERED GLASS
DIMMERABILE - DIMMABLE

APPARECCHIO CON COPERTURA IN ALLUMINIO
24VDC
LUMINAIRE WITH ALUMINIUM COVER
24VDC



CODICE CODE	FASCIO BEAM	WATT	SORGENTE SOURCE	APPARECCHIO FIXTURE	ALIMENTAZIONE POWER SUPPLY	CL	IP	IK	CRI
1051W/▲RRCVO	 DIFFUSO/110° DIFFUSED/110°	3,5W	500 lm	180 lm	24Vdc	III	66	07	>80

VO = VETRO EXTRACHIARO OPALE TEMPRATO - VO = EXTRA CLEAR OPAL TEMPERED GLASS
DIMMERABILE - DIMMABLE

APPARECCHIO CON COPERTURA IN NYLON
24VDC
LUMINAIRE WITH NYLON COVER
24VDC



CODICE CODE	FASCIO BEAM	WATT	SORGENTE SOURCE	APPARECCHIO FIXTURE	ALIMENTAZIONE POWER SUPPLY	CL	IP	IK	CRI
1052W/▲RRCVO	 DIFFUSO/110° DIFFUSED/110°	3,5W	500 lm	180 lm	24Vdc	III	66	07	>80

VO = VETRO EXTRACHIARO OPALE TEMPRATO - VO = EXTRA CLEAR OPAL TEMPERED GLASS
DIMMERABILE - DIMMABLE

ACCESSORI
ACCESSORIES

E.TRA.647 1 DRIVER FOR 1-3 LAMPS	ALIMENTATORE PER BOX 12W 24VDC IP65 - ON/OFF DRIVER FOR BOX 12W 24VDC IP65 - ON/OFF	E.TRA.579 1 DRIVER FOR 7-20 LAMPS	ALIMENTATORE ON/OFF 100W 24VDC IP67 DRIVER ON/OFF 100W 24VDC IP67
E.TRA.631 1 DRIVER FOR 1-3 LAMPS	ALIMENTATORE ON/OFF 15W 24VDC IP20 DRIVER ON/OFF 15W 24VDC IP20	E.TRA.633 1 DRIVER FOR 1-20 LAMPS	ALIMENTATORE DALI 100W 24VDC IP67 DRIVER DALI 100W 24VDC IP67
E.TRA.577 1 DRIVER FOR 1-6 LAMPS	ALIMENTATORE ON/OFF 25W 24VDC IP67 DRIVER ON/OFF 25W 24VDC IP67		

APPARECCHIO CON COPERTURA IN ACCIAIO
LED DIRECT AC

LUMINAIRE WITH STEEL COVER
LED DIRECT AC



CODICE CODE	FASCIO BEAM	WATT	SORGENTE SOURCE	APPARECCHIO FIXTURE	ALIMENTAZIONE POWER SUPPLY	CL	IP	IK	CRI
1050W/WRACVO	 DIFFUSO/110° DIFFUSED/110°	5W	500 lm	180 lm	220-240Vac 50/60Hz	II	66	07	>80

VO = VETRO EXTRACHIARO OPALE TEMPRATO - VO = EXTRA CLEAR OPAL TEMPERED GLASS
DIMMERABILE IN TAGLIO DI FASE - PHASE CUT DIMMABLE

APPARECCHIO CON COPERTURA IN ALLUMINIO
LED DIRECT AC

LUMINAIRE WITH ALUMINIUM COVER
LED DIRECT AC



CODICE CODE	FASCIO BEAM	WATT	SORGENTE SOURCE	APPARECCHIO FIXTURE	ALIMENTAZIONE POWER SUPPLY	CL	IP	IK	CRI
1051W/WRACVO	 DIFFUSO/110° DIFFUSED/110°	5W	500 lm	180 lm	220-240Vac 50/60Hz	II	66	07	>80

VO = VETRO EXTRACHIARO OPALE TEMPRATO - VO = EXTRA CLEAR OPAL TEMPERED GLASS
DIMMERABILE IN TAGLIO DI FASE - PHASE CUT DIMMABLE

APPARECCHIO CON COPERTURA IN NYLON
LED DIRECT AC

LUMINAIRE WITH NYLON COVER
LED DIRECT AC



CODICE CODE	FASCIO BEAM	WATT	SORGENTE SOURCE	APPARECCHIO FIXTURE	ALIMENTAZIONE POWER SUPPLY	CL	IP	IK	CRI
1052W/WRACVO	 DIFFUSO/110° DIFFUSED/110°	5W	500 lm	180 lm	220-240Vac 50/60Hz	II	66	07	>80

VO = VETRO EXTRACHIARO OPALE TEMPRATO - VO = EXTRA CLEAR OPAL TEMPERED GLASS
DIMMERABILE IN TAGLIO DI FASE - PHASE CUT DIMMABLE

ACCESSORI
ACCESSORIES

E.TRA.581	LIMITATORE DI SOVRATENSIONE CL II - IP67 SURGE PROTECTOR CL II - IP67
-----------	--

APPARECCHIO CON COPERTURA IN ACCIAIO**DRIVER INCORPORATO***LUMINAIRE WITH STEEL COVER**BUILT-IN DRIVER*

REVIEW



CODICE CODE	FASCIO BEAM	WATT	SORGENTE SOURCE	APPARECCHIO FIXTURE	ALIMENTAZIONE POWER SUPPLY	CL	IP	IK	CRI
1050W/▲C20NB	STRETTO/12° NARROW/12°	5W	530 lm	480 lm	220-240Vac 50/60Hz	II	66	07	>80
1050W/▲C20MB	MEDIO/26° MEDIUM/26°	5W	530 lm	470 lm	220-240Vac 50/60Hz	II	66	07	>80
1050W/▲C20WB	LARGO/52° WIDE/52°	5W	530 lm	455 lm	220-240Vac 50/60Hz	II	66	07	>80

VETRO EXTRACHIARO TRASPARENTE TEMPRATO – EXTRA CLEAR TRANSPARENT TEMPERED GLASS

ON/OFF

APPARECCHIO CON COPERTURA IN ALLUMINIO**DRIVER INCORPORATO***LUMINAIRE WITH ALUMINIUM COVER**BUILT-IN DRIVER*

REVIEW



CODICE CODE	FASCIO BEAM	WATT	SORGENTE SOURCE	APPARECCHIO FIXTURE	ALIMENTAZIONE POWER SUPPLY	CL	IP	IK	CRI
1051W/▲C20NB	STRETTO/12° NARROW/12°	5W	530 lm	480 lm	220-240Vac 50/60Hz	II	66	07	>80
1051W/▲C20MB	MEDIO/26° MEDIUM/26°	5W	530 lm	470 lm	220-240Vac 50/60Hz	II	66	07	>80
1051W/▲C20WB	LARGO/52° WIDE/52°	5W	530 lm	455 lm	220-240Vac 50/60Hz	II	66	07	>80

VETRO EXTRACHIARO TRASPARENTE TEMPRATO – EXTRA CLEAR TRANSPARENT TEMPERED GLASS

ON/OFF

APPARECCHIO CON COPERTURA IN NYLON**DRIVER INCORPORATO***LUMINAIRE WITH NYLON COVER**BUILT-IN DRIVER*

REVIEW



CODICE CODE	FASCIO BEAM	WATT	SORGENTE SOURCE	APPARECCHIO FIXTURE	ALIMENTAZIONE POWER SUPPLY	CL	IP	IK	CRI
1052W/▲C20NB	STRETTO/12° NARROW/12°	5W	530 lm	480 lm	220-240Vac 50/60Hz	II	66	07	>80
1052W/▲C20MB	MEDIO/26° MEDIUM/26°	5W	530 lm	470 lm	220-240Vac 50/60Hz	II	66	07	>80
1052W/▲C20WB	LARGO/52° WIDE/52°	5W	530 lm	455 lm	220-240Vac 50/60Hz	II	66	07	>80

VETRO EXTRACHIARO TRASPARENTE TEMPRATO – EXTRA CLEAR TRANSPARENT TEMPERED GLASS

ON/OFF

ACCESSORI*ACCESSORIES*

E.TRA.581	LIMITATORE DI SOVRATENSIONE CL II – IP67 SURGE PROTECTOR CL II – IP67
------------------	--

ACCESSORI

ACCESSORIES

ALIMENTATORI 24Vdc

DRIVER 24Vdc

**E.TRA.577**

1 Driver for 1-6 Lamps

Alimentatore ON/OFF 25W 24Vdc IP67

Driver ON/OFF 25W 24Vdc IP67

L 148 x W 40 x H 32

**E.TRA.579**

1 Driver for 7-20 Lamps

Alimentatore ON/OFF 100W 24Vdc IP67

Driver ON/OFF 100W 24Vdc IP67

L 140 x W 63 x H 32

**E.TRA.631**

1 Driver for 1-3 Lamps

Alimentatore ON/OFF 15W 24Vdc IP20

Driver ON/OFF 15W 24Vdc IP20

L 106 x W 33 x H 22

**E.TRA.633**

1 Driver for 1-20 Lamps

Alimentatore DALI 100W 24Vdc IP67

Driver DALI 100W 24Vdc IP67

L 175 x W 63 x H 36

**E.TRA.647**

1 Driver for 1-3 Lamps

Alimentatore per Box 12W 24Vdc IP65 - ON/OFF

Driver for Box 12W 24Vdc IP65 - ON/OFF

L 57 x W 40 x H 26

PROTEZIONE ALLE SOVRATENSIONI

SURGE PROTECTOR

**E.TRA.581**

Limitatore di sovratensione CL II - IP67

Surge protector CL II - IP67

L 37 x W 30 x H 30

